

Overview

Models

HP 5500-24G SI Switch with 2 Interface Slots	JD369A
HP 5500-48G SI Switch with 2 Interface Slots	JD370A
HP 5500-24G-PoE+ SI Switch with 2 Interface Slots	JG238A
HP 5500-48G-PoE+ SI Switch with 2 Interface Slots	JG239A

Key features

- Managed Layer 2 and Layer 3 GbE connectivity
- High performance
- Enterprise-class security features
- Application convergence capable
- Easy to use and manage

Product overview

These Gigabit Ethernet switches deliver quad-speed performance, 10/100/1000 and 10 Gigabit Ethernet, as well as advanced voice-enhanced features such as Power over Ethernet (PoE), auto-voice VLAN, and Quality of Service (QoS). As a result, they are ideal for enterprise organizations seeking to build a secure, convergence-enhanced campus network. Robust IPv6 support and 10 Gigabit Ethernet uplinks future-proof an enterprise network against obsolescence. Resilient Ring Protection Protocol (RRPP), Smart Link, and Intelligent Resilient Framework (IRF) deliver 50 ms switchover and carrier-class reliability.

Features and benefits

Quality of Service (QoS)

- **Broadcast control:** allows limitation of broadcast traffic rate to cut down on unwanted broadcast traffic on the network
- **Advanced classifier-based QoS:** classifies traffic using multiple match criteria based on Layer 2, 3, and 4 information; applies QoS policies such as setting priority level and rate limit to selected traffic on a port, VLAN, or whole switch
- **Powerful QoS feature:** supports the following congestion actions: strict priority queuing (SP), weighted round robin queuing, and SP+WRR
- **Traffic policing:** supports Committed Access Rate (CAR) and line rate

Management

- **Friendly port names:** allow assignment of descriptive names to ports
- **Remote configuration and management:** is available through a secure Web browser or a CLI
- **Manager and operator privilege levels:** enable read-only (operator) and read/write (manager) access on CLI and Web browser management interfaces
- **Command authorization:** leverages HWTACACS to link a custom list of CLI commands to an individual network administrator's login; also provides an audit trail
- **Secure Web GUI:** provides a secure, easy-to-use graphical interface for configuring the module via HTTPS
- **Multiple configuration files:** can be stored to the flash image
- **Complete session logging:** provides detailed information for problem identification and resolution
- **SNMPv1, v2c, and v3:** facilitate centralized discovery, monitoring, and secure management of networking devices

Overview

- **Remote monitoring (RMON):** uses standard SNMP to monitor essential network functions; supports events, alarm, history, and statistics group plus a private alarm extension group
- **IEEE 802.1AB Link Layer Discovery Protocol (LLDP):** advertises and receives management information from adjacent devices on a network, facilitating easy mapping by network management applications
- **sFlow (RFC 3176):** provides scalable ASIC-based wirespeed network monitoring and accounting with no impact on network performance; this allows network operators to gather a variety of sophisticated network statistics and information for capacity planning and real-time network monitoring purposes
- **Management VLAN:** segments traffic to and from management interfaces, including CLI/telnet, a Web browser interface, and SNMP
- **Remote Intelligent Mirroring:** mirrors ingress/egress ACL-selected traffic from a switch port or VLAN to a local or remote switch port anywhere on the network
- **Device Link Detection Protocol (DLDP):** monitors a cable between two switches and shuts down the ports on both ends if the cable is broken, preventing network problems such as loops
- **IPv6 management:** future-proofs networking, as the switch is capable of being managed whether the attached network is running IPv4 or IPv6; supports pingv6, tracertv6, Telnetv6, TFTPv6, DNSv6, syslogv6, FTPv6, SNMPv6, DHCPv6, and RADIUS for IPv6
- **Troubleshooting:** ingress and egress port monitoring enable network problem solving; virtual cable tests provide visibility into cable problems

Connectivity

- **Auto-MDIX:** automatically adjusts for straight-through or crossover cables on all 10/100/1000 ports
- **Flow control:** provides back pressure using standard IEEE 802.3x, reducing congestion in heavy traffic situations
- **Ethernet operations, administration and maintenance (OAM)**
detects data link layer problems that occurred in the "last mile" using the IEEE 802.3ah OAM standard; monitors the status of the link between two devices
- **Jumbo packet support:** supports up to 9216-byte frame size to improve the performance of large data transfers
- **Optional 10 GbE ports:** deliver, through the use of optional modules, additional 10GbE connections, which are available for uplinks or high-bandwidth server connections; flexibly support copper, XFP, SFP+, or CX4 local connections
- **IEEE 802.3at Power over Ethernet (PoE+) support:** simplifies deployment and dramatically reduces installation costs by helping to eliminate the time and cost involved in supplying local power at each access point location
- **High-bandwidth CX4 local stacking:** when stacked using CX4 local stacking, achieves 12 Gbps per connection, allowing for up to 96 Gbps total stacking bandwidth (full duplex) in a resilient stacking configuration

Performance

- **Nonblocking architecture**
up to 192 Gbps nonblocking switching fabric provides wire-speed switching with up to 143 million pps throughput
- **Hardware-based wirespeed access control lists (ACLs)**
help provide high levels of security and ease of administration without impacting network performance with a feature-rich TCAM-based ACL implementation

Resiliency and high availability

- **Separate data and control paths:** keeps control separated from services and keeps service processing isolated; increases security and performance
- **External redundant power supply:** provides high reliability
- **Smart link:** allows 50 ms failover between links
- **Spanning Tree/MSTP and RSTP:** provide redundant links while preventing network loops
- **Rapid Ring Protection Protocol (RRPP):** connects multiple switches in a high-performance ring using standard Ethernet

Overview

technology; traffic can be rerouted around the ring in less than 50 ms, reducing the impact on traffic and applications

- **Intelligent Resilient Framework (IRF):** creates virtual resilient switching fabrics, where two or more switches perform as a single L2 switch and L3 router; switches do not have to be co-located and can be part of a disaster recovery system; servers or switches can be attached using standard LACP for automatic load balancing and high availability; can eliminate the need for complex protocols like Spanning Tree Protocol, Equal-Cost Multipath (ECMP), or VRRP, thereby simplifying network operation

Layer 2 switching

- **16K MAC address table:** provides access to many Layer 2 devices
- **VLAN support and tagging:** support IEEE 802.1Q, with 4,094 simultaneous VLAN IDs
- **GARP VLAN Registration Protocol:** allows automatic learning and dynamic assignment of VLANs
- **IEEE 802.1ad QinQ and Selective QinQ:** increase the scalability of an Ethernet network by providing a hierarchical structure; connect multiple LANs on a high-speed campus or metro network
- **10GbE port aggregation**
allows grouping of ports to increase overall data throughput to a remote device
- **Internet Group Management Protocol (IGMP) and Multicast Listener Discovery (MLD) protocol snooping:** effectively control and manage the flooding of multicast packets in a Layer 2 network

Layer 3 services

- **Address Resolution Protocol (ARP):** determines the MAC address of another IP host in the same subnet
- **Dynamic Host Configuration Protocol (DHCP):** simplifies the management of large IP networks; supports client; DHCP Relay enables DHCP operation across subnets
- **Loopback interface address:** defines an address in RIP that can always be reachable, improving diagnostic capability
- **User Datagram Protocol (UDP) helper function:** allows User Datagram Protocol (UDP) broadcasts to be directed across router interfaces to specific IP unicast or subnet broadcast addresses and prevents server spoofing for UDP services such as DHCP
- **Route maps:** provide more control during route redistribution; allow filtering and altering of route metrics

Layer 3 routing

- **IPv4 routing protocols:** support static routes and RIP
- **IPv6 routing protocols:** provide routing of IPv6 at wire speed; support static routes and RIPng

Security

- **Access control lists (ACLs):** provide IP Layer 2 to Layer 4 traffic filtering; support global ACL, VLAN ACL, port ACL, and IPv6 ACL
- **IEEE 802.1X:** industry-standard method of user authentication using an IEEE 802.1X supplicant on the client in conjunction with a RADIUS server
- **MAC-based authentication:** authenticates the client with the RADIUS server based on the client's MAC address
- **Identity-driven security and access control:**
 - **Per-user ACLs:** permit or deny user access to specific network resources based on user identity and time of day, allowing multiple types of users on the same network to access specific network services without risking network security or providing unauthorized access to sensitive data
 - **Automatic VLAN assignment:** automatically assigns users to the appropriate VLAN based on their identities
- **Secure management access:** securely encrypts all access methods (CLI, GUI, or MIB) through SSHv2, SSL, and/or SNMPv3
- **Secure FTP:** allows secure file transfer to and from the switch; protects against unwanted file downloads or unauthorized copying of a switch configuration file
- **Guest VLAN:** provides a browser-based environment to authenticated clients that is similar to IEEE 802.1X
- **Endpoint Admission Defense (EAD):** provides security policies to users accessing a network
- **Port security:** allows access only to specified MAC addresses, which can be learned or specified by the administrator

Overview

- **Port isolation:** secures and adds privacy, and prevents malicious attackers from obtaining user information
- **STP BPDU port protection:** blocks Bridge Protocol Data Units (BPDUs) on ports that do not require BPDUs, preventing forged BPDU attacks
- **STP Root Guard:** protects the root bridge from malicious attacks or configuration mistakes
- **DHCP protection:** blocks DHCP packets from unauthorized DHCP servers, preventing denial-of-service attacks
- **Dynamic ARP protection:** blocks ARP broadcasts from unauthorized hosts, preventing eavesdropping or theft of network data
- **IP Source Guard:** helps prevent IP spoofing attacks
- **RADIUS/HWTACACS:** eases switch management security administration by using a password authentication server

Convergence

- **IEEE 802.1AB Link Layer Discovery Protocol (LLDP):** is an automated device discovery protocol that provides easy mapping of network management applications
- **LLDP-MED:** is a standard extension that automatically configures network devices, including LLDP-capable IP phones
- **LLDP-CDP compatibility:** receives and recognizes CDP packets from Cisco's IP phones for seamless interoperation
- **IEEE 802.3af Power over Ethernet:** provides up to 15.4 W per port to PoE-powered devices such as IP phones, wireless access points, and video cameras
- **PoE allocations:** support multiple methods (automatic, IEEE 802.3af class, LLDP-MED, or user specified) to allocate PoE power for more efficient energy savings
- **Voice VLAN:** automatically assigns VLAN and priority for IP phones, simplifying network configuration and maintenance
- **IP multicast snooping (data-driven IGMP):** automatically prevents flooding of IP multicast traffic
- **Multicast VLAN:** allows multiple VLANs to receive the same IPv4 or IPv6 multicast traffic, lessening network bandwidth demand by reducing or eliminating multiple streams to each VLAN

Device support

- **Cisco prestandard PoE support:** detects and provides power to Cisco's prestandard PoE devices such as wireless LAN access points and IP phones

Additional information

- **Green IT and power:** use the latest advances in silicon development, shut off unused ports, and use variable-speed fans to improve power efficiency
- **Green initiative support:** provides support for RoHS and WEEE regulations
- **Warranty and support**

Lifetime Warranty 2.0

advance hardware replacement for as long as you own the product with next-business-day delivery (available in most countries)†

- **Electronic and telephone support (for Lifetime Warranty 2.0)**

limited 24x7 telephone support is available from HP for the first 3 years; limited electronic and business hours telephone support is available from HP for the entire warranty period; to reach our support centers, refer to www.hp.com/networking/contact-support; for details on the duration of support provided with your product purchase, refer to www.hp.com/networking/warrantysummary

- **Software releases**

to find software for your product, refer to www.hp.com/networking/support; for details on the software releases available with your product purchase, refer to www.hp.com/networking/warrantysummary

†HP warranty includes repair or replacement of hardware for as long as you own the product, with next business day advance replacement (available in most countries). The disk drive included with HP AllianceOne Advanced Services and Services zL Modules, HP Threat Management Services zL Module, HP AllianceOne Extended zL Module with Riverbed Steelhead, HP MSM765 zL Mobility Controller

Overview

and HP Survivable Branch Communication zl Module powered by Microsoft® Lync has a five-year hardware warranty. For details, refer to the Software license and hardware warranty statements at www.hp.com/networking/warranty.

Configuration

Build To Order:

BTO is a standalone unit with no integration. BTO products ship standalone are not part of a CTO or Rack-Shippable solution.

Switch Chassis

HP 5500-24G-PoE SI Switch

- 24 RJ-45 autosensing 10/100/1000 ports
- 4 dual-personality ports; PoE auto-sensing 10/100/1000Base-T or SFP
- min=0 \ max=4 SFP Transceivers
- 2 port expansion module slots
- 1U - Height

JD371A

See Configuration Note:1,
3

HP 5500-24G SI Switch

- 24 RJ-45 autosensing 10/100/1000 ports
- 4 dual-personality ports; PoE auto-sensing 10/100/1000Base-T or SFP
- min=0 \ max=4 SFP Transceivers
- 2 port expansion module slots
- 1U - Height

JD369A

See Configuration Note:1,
3

HP 5500-24G-PoE+ SI Switch w/2 Intf Slts

- 24 RJ-45 autosensing 10/100/1000 ports
- 4 dual-personality ports; PoE auto-sensing 10/100/1000Base-T or SFP
- min=0 \ max=4 SFP Transceivers
- 2 port expansion module slots
- 1U - Height

JD238A

See Configuration Note:1,
3

HP 5500-48G-PoE SI Switch

- 48 RJ-45 autosensing 10/100/1000 ports
- 4 dual-personality ports; PoE auto-sensing 10/100/1000Base-T or SFP
- min=0 \ max=4 SFP Transceivers
- 2 port expansion module slots
- 1U - Height

JD372A

See Configuration Note:1,
3

HP 5500-48G SI Switch

- 48 RJ-45 autosensing 10/100/1000 ports
- 4 dual-personality ports; PoE auto-sensing 10/100/1000Base-T or SFP
- min=0 \ max=4 SFP Transceivers
- 2 port expansion module slots
- 1U - Height

JD370A

See Configuration Note:1,
3

HP 5500-48G-PoE+ SI Switch w/2 Intf Slts

- 48 RJ-45 autosensing 10/100/1000 ports
- 4 dual-personality ports; PoE auto-sensing 10/100/1000Base-T or SFP
- min=0 \ max=4 SFP Transceivers
- 2 port expansion module slots
- 1U - Height

JD239A

See Configuration Note:1,
3

Configuration

Configuration Rules:

Note 1	The following Transceivers install into this Switch:	
	HP X125 1G SFP LC LH40 1310nm Transceiver	JD061A
	HP X120 1G SFP LC LH40 1550nm Transceiver	JD062A
	HP X120 1G SFP LC SX Transceiver	JD118B
	HP X120 1G SFP LC LX Transceiver	JD119B
	HP X120 1G SFP LC BX 10-U Transceiver	JD098B
	HP X120 1G SFP LC BX 10-D Transceiver	JD099B
	HP X120 1G SFP RJ45 T Transceiver	JD089B
	HP X110 100M SFP LC FX Dual Mode Transceiver	JD497B
	HP X110 100M SFP LC LX Dual Mode Transceiver	JD498B
	HP X125 1G SFP LC LH70 Transceiver	JD063B

Note 2 Localization required. (See Localization Menu for list.)

Remarks: If any TAA product is selected please display the following note; 'This product is intended for Government sales.'

Internal Power Supplies

Power Supplies included

Enter the following menu selections as integrated to the CTO Model X server above if order is factory built.

Modules

User Selection (min 0 / max=2) per Chassis

HP 5500 2-port 10GbE XFP Module	JD359B
<ul style="list-style-type: none">min=0 \ max=2 XFP Transceivers	See Configuration Note:2
HP 5500 2-port 10GbE Local Connect Mod	JD360B
<ul style="list-style-type: none">min=0 \ max=2 CX4 Cables	See Configuration Note:4
HP 5500 1-port 10GbE XFP Module	JD361B
<ul style="list-style-type: none">min=0 \ max=1 XFP Transceivers	See Configuration Note:2
HP 2p 10-GbE SFP+ A5500/E4800/E4500 Mod	JD368B
<ul style="list-style-type: none">min=0 \ max=2 SFP+ Transceivers	See Configuration Note:1
HP 5500/4800 2-port GbE SFP Module	JD367A
<ul style="list-style-type: none">min=0 \ max=2 SFP Transceivers	See Configuration Note:3

Configuration

HP 5500/5120 2p 10GBASE-T Module

JG535A

- No Transceivers

Configuration Rules:

Note 1	The following Transceivers install into this Module:	
	HP X130 10G SFP+ LC ER 40km Transceiver	JG234A
	HP X130 SFP+ LC SR Transceiver	JD092B
	HP X130 SFP+ LC LRM Transceiver	JD093B
	HP X130 SFP+ LC LR Transceiver	JD094B
	HP X240 10G SFP+ SFP+ 5m DAC Cable	JG081C
	HP X240 10G SFP+ 7m DAC Cable	JC784C
Note 2	The following Transceivers install into this Module:	
	HP X135 10G XFP LC ER Transceiver	JD121A
	HP X130 10G XFP SC LR 1310nm Transceiver	JD108B
	HP X130 10G XFP LC SR Transceiver	JD117B
Note 3	The following Transceivers install into this Module:	
	HP X125 1G SFP LC LH40 1310nm Transceiver	JD061A
	HP X120 1G SFP LC LH40 1550nm Transceiver	JD062A
	HP X120 1G SFP LC SX Transceiver	JD118B
	HP X120 1G SFP LC LX Transceiver	JD119B
	HP X120 1G SFP LC BX 10-U Transceiver	JD098B
	HP X120 1G SFP LC BX 10-D Transceiver	JD099B
	HP X120 1G SFP RJ45 T Transceiver	JD089B
	HP X110 100M SFP LC FX Dual Mode Transceiver	JD497B
	HP X110 100M SFP LC LX Dual Mode Transceiver	JD498B
	HP X125 1G SFP LC LH70 Transceiver	JD063B
Note 4	The following Cables install into this Module:	
	HP X230 Local Connect 50cm CX4 Cable	JD363B
	HP X230 Local Connect 100cm CX4 Cable	JD364B
	HP X230 CX4 to CX4 3m Cable	JD365A
	NOTE: Two JD365A - HP X230 CX4 to CX4 3m Cable should be added by default if Module is selected.	

Transceivers

SFP Transceivers

HP X120 1G SFP LC SX Transceiver	JD118B
HP X120 1G SFP LC LX Transceiver	JD119B

Configuration

HP X120 1G SFP LC LH40 1550nm XCVR	JD062A
HP X125 1G SFP LC LH40 1310nm XCVR	JD061A
HP X120 1G SFP LC BX 10-U Transceiver	JD098B
HP X120 1G SFP LC BX 10-D Transceiver	JD099B
HP X120 1G SFP RJ45 T Transceiver	JD089B
HP X125 1G SFP LC LH70 Transceiver	JD063B

Configuration Rules:

SFP+ Transceivers

HP X130 10G SFP+ LC ER 40km Transceiver	JG234A
HP X130 SFP+ LC SR Transceiver	JD092B
HP X130 SFP+ LC LRM Transceiver	JD093B
HP X130 SFP+ LC LR Transceiver	JD094B
HP X240 10G SFP+ SFP+ 5m DAC Cable	JG081C
HP X240 10G SFP+ 7m DAC Cable	JC784C

XFP Transceivers

HP X130 10G XFP LC LR 1310nm Transceiver	JD108B
HP X130 LC SR XFP Transceiver	JD117B
HP X135 10G XFP LC ER Transceiver	JD121A

Cables

Local Connect Cables

HP X230 Local Connect 50cm CX4 Cable	JD363B
HP X230 Local Connect 100cm CX4 Cable	JD364B
HP X230 Local Connect 50cm CX4 Cable	JD365A

Multi-Mode Cables

HP .5m Multi-mode OM3 LC/LC FC Cable	AJ833A
HP 1m Multi-mode OM3 LC/LC FC Cable	AJ834A
HP 2 m Multimode OM3 LC/LC FC Cable	AJ835A
HP 5 m Multimode OM3 LC/LC FC Cable	AJ836A
HP 15 m Multimode OM3 LC/LC FC Cable	AJ837A
HP 30 m Multimode OM3 LC/LC FC Cable	AJ838A
HP 50 m Multimode OM3 LC/LC FC Cable	AJ839A
HP Premier Flex LC/LC OM4 2f 1m Cbl	QK732A
HP Premier Flex LC/LC OM4 2f 2m Cbl	QK733A
HP Premier Flex LC/LC OM4 2f 5m Cbl	QK734A
HP Premier Flex LC/LC OM4 2f 15m Cbl	QK735A

Configuration

HP Premier Flex LC/LC OM4 2f 30m Cbl	QK736A
HP Premier Flex LC/LC OM4 2f 50m Cbl	QK737A
HP Premier Flex LC/LC OM4 2f 1m Cbl	QK732A

Switch Enclosure Options

External/Redundant Power Supplies

HP RPS 800 Redundant Power Supply	JD183A
<ul style="list-style-type: none">• Height = 1U• includes 1 x c13, 800w	See Configuration Note:2, 3
HP RPS1600 Redundant Power System	JG136A
<ul style="list-style-type: none">• Height = 1U• includes 1 x c13, 1600w and Power Supply port	See Configuration Note:2, 4
HP RPS1600 1600W AC Power Supply	JG137A
<ul style="list-style-type: none">• Installs into JG136A only	See Configuration Note:1

Configuration Rules:

Note 1	If this power supply is selected, The JG136A - HP A-RPS1600 Redundant Power System must be on order or onsite.
Note 2	Localization required.
Note 3	Supported only on the JD369A and JD370A Switches
Note 4	Supported only on the JD369A, JD370A, JD371A, JD372A, JG238A and JG239A Switches.

Options for External/Redundant Power Supplies

HP X290 1000 A JD5 2m RPS Cable	JD187A
HP X290 500 C 1m RPS Cable	JD184A

Technical Specifications

HP 5500-24G SI Switch with 2 Interface Slots (JD369A)

Ports	24 autosensing 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only 4 dual-personality ports; auto-sensing 10/100/1000Base-T or SFP 2 port expansion module slots 1 RJ-45 serial console port Supports a maximum of 24 autosensing 10/100/1000 ports	
Physical characteristics	Dimensions	17.32(w) x 11.81(d) x 1.72(h) in (44 x 30 x 4.36 cm) (1U height)
	Weight	9.92 lb (4.5 kg)
Memory and processor	128 MB SDRAM, 16 MB flash; packet buffer size: 2 MB	
Mounting	Mounts in an EIA standard 19-in. telco rack or equipment cabinet (hardware included)	
Performance	1000 Mb Latency	< 3.2 μ s
	10 Gbps Latency	< 2.6 μ s
	Throughput	107.2 million pps
	Routing/Switching capacity	144 Gb/s
Environment	Operating temperature	32°F to 113°F (0°C to 45°C)
	Operating relative humidity	10% to 90%, noncondensing
	Nonoperating/Storage temperature	-40°F to 158°F (-40°C to 70°C)
	Nonoperating/Storage relative humidity	5% to 95%, noncondensing
	Acoustic	ISO 7779
Electrical characteristics	Maximum heat dissipation	273 BTU/hr (288.02 kJ/hr)
	Voltage	100-240 VAC
	Maximum power rating	80 W
	Frequency	50/60 Hz
	Notes	Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.
Safety	UL 60950-1; EN 60825-1 Safety of Laser Products-Part 1; EN 60825-2 Safety of Laser Products-Part 2; IEC 60950-1; CAN/CSA-C22.2 No. 60950-1; EN 60950-1/A11; FDA 21 CFR Subchapter J; ROHS Compliance	
Emissions	FCC part 15 Class A; VCCI Class A; EN 55022 Class A; CISPR 22 Class A; ICES-003 Class A; ANSI C63.4 2003; ETSI EN 300 386 V1.3.3; AS/NZS CISPR22 Class A; EN 61000-3-2; EN 61000-3-3; EN 61000-4-2; EN 61000-4-3; EN 61000-4-4; EN 61000-4-5; EN 61000-4-6; EN 61000-4-11; EN 61000-3-2:2006; EN 61000-3-3:1995 +A1:2001 +A2:2005; EMC Directive 2004/108/EC; FCC (CFR 47, Part 15) Class A	
Management	IMC - Intelligent Management Center; command-line interface; Web browser; SNMP Manager	
Services	3-year, 4-hour onsite, 13x5 coverage for hardware (UV870E) 3-year, 4-hour onsite, 24x7 coverage for hardware (UV873E)	

Technical Specifications

- 3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 SW phone support and SW updates (UV876E)
- 3-year, 24x7 SW phone support, software updates (UV879E)
- 1-year, post-warranty, 4-hour onsite, 13x5 coverage for hardware (HR574E)
- 1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware (HR575E)
- 1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (HR576E)
- Installation with minimum configuration, system-based pricing (UW451E)
- 4-year, 4-hour onsite, 13x5 coverage for hardware (UV871E)
- 4-year, 4-hour onsite, 24x7 coverage for hardware (UV874E)
- 4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UV877E)
- 4-year, 24x7 SW phone support, software updates (UV880E)
- 5-year, 4-hour onsite, 13x5 coverage for hardware (UV872E)
- 5-year, 4-hour onsite, 24x7 coverage for hardware (UV875E)
- 5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UV878E)
- 5-year, 24x7 SW phone support, software updates (UV881E)
- 3 Yr 6 hr Call-to-Repair Onsite (UW966E)
- 4 Yr 6 hr Call-to-Repair Onsite (UW967E)
- 5 Yr 6 hr Call-to-Repair Onsite (UW968E)
- 1-year, 6 hour Call-To-Repair Onsite for hardware (HR578E)
- 1-year, 24x7 software phone support, software updates (HR577E)
- 1-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS658E)
- 1-year, 24x7 software phone support, software updates + 4 hour hardware exchange (HS659E)
- 3-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS660E)
- 3-year, 24x7 software phone support, software updates + 4 hour Hardware Exchange (HS661E)
- 4-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS662E)
- 4-year, 24x7 software phone support, software updates + 4 hour Hardware Exchange (HS663E)
- 5-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS664E)
- 5-year, 24x7 software phone support, software updates + 4 hour Hardware Exchange (HS665E)

Refer to the HP website at: www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

HP 5500-48G SI Switch with 2 Interface Slots (JD370A)

Ports	48 RJ-45 autosensing 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T); Media Type: Auto-MDIX; Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only	
	4 dual-personality ports; auto-sensing 10/100/1000Base-T or SFP	
	2 port expansion module slots	
	1 RJ-45 serial console port	
	Supports a maximum of 48 autosensing 10/100/1000 ports	
Physical characteristics	Dimensions	17.32(w) x 11.81(d) x 1.72(h) in (44 x 30 x 4.36 cm) (1U height)
	Weight	11.02 lb (5 kg)
Memory and processor	128 MB SDRAM, 16 MB flash; packet buffer size: 4 MB	

Technical Specifications

Mounting	Mounts in an EIA standard 19-in. telco rack or equipment cabinet (hardware included)	
Performance	1000 Mb Latency	< 3.2 μ s
	10 Gbps Latency	< 2.6 μ s
	Throughput	142.9 million pps
	Routing/Switching capacity	192 Gb/s
Environment	Operating temperature	32°F to 113°F (0°C to 45°C)
	Operating relative humidity	10% to 90%, noncondensing
	Nonoperating/Storage temperature	-40°F to 158°F (-40°C to 70°C)
	Nonoperating/Storage relative humidity	5% to 95%, noncondensing
	Acoustic	ISO 7779
Electrical characteristics	Maximum heat dissipation	410 BTU/hr (432.55 kJ/hr)
	Voltage	100-240 VAC
	Maximum power rating	120 W
	Frequency	50/60 Hz
	Notes	Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.
Safety	UL 60950-1; EN 60825-1 Safety of Laser Products-Part 1; EN 60825-2 Safety of Laser Products-Part 2; IEC 60950-1; CAN/CSA-C22.2 No. 60950-1; EN 60950-1/A11; FDA 21 CFR Subchapter J; ROHS Compliance	
Emissions	FCC part 15 Class A; VCCI Class A; EN 55022 Class A; CISPR 22 Class A; ICES-003 Class A; ANSI C63.4 2003; ETSI EN 300 386 V1.3.3; AS/NZS CISPR22 Class A; EN 61000-3-2; EN 61000-3-3; EN 61000-4-2; EN 61000-4-3; EN 61000-4-4; EN 61000-4-5; EN 61000-4-6; EN 61000-4-11; EN 61000-3-2:2006; EN 61000-3-3:1995 +A1:2001 +A2:2005; EMC Directive 2004/108/EC; FCC (CFR 47, Part 15) Class A	
Management	IMC - Intelligent Management Center; command-line interface; Web browser; SNMP Manager	
Services	3-year, 4-hour onsite, 13x5 coverage for hardware (HQ080E)	
	3-year, 4-hour onsite, 24x7 coverage for hardware (HQ081E)	
	3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 SW phone support and SW updates (HQ084E)	
	3-year, 24x7 SW phone support, software updates (HQ083E)	
	1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware (HR580E)	
	1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (HR581E)	
	Installation with minimum configuration, system-based pricing (UW451E)	
	4-year, 4-hour onsite, 13x5 coverage for hardware (HQ085E)	
	4-year, 4-hour onsite, 24x7 coverage for hardware (HQ086E)	
	4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (HQ093E)	
	4-year, 24x7 SW phone support, software updates (HQ091E)	
	5-year, 4-hour onsite, 13x5 coverage for hardware (HQ088E)	
5-year, 4-hour onsite, 24x7 coverage for hardware (HQ089E)		
5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (HQ094E)		

Technical Specifications

- 5-year, 24x7 SW phone support, software updates (HQ092E)
- 3 Yr 6 hr Call-to-Repair Onsite (HQ082E)
- 4 Yr 6 hr Call-to-Repair Onsite (HQ087E)
- 5 Yr 6 hr Call-to-Repair Onsite (HQ090E)
- 1-year, 4-hour onsite, 13x5 coverage for hardware (HR579E)
- 1-year, 6 hour Call-To-Repair Onsite for hardware (HR583E)
- 1-year, 24x7 software phone support, software updates (HR582E)
- 1-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS674E)
- 1-year, 24x7 software phone support, software updates + 4 hour hardware exchange (HS675E)
- 3-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS676E)
- 3-year, 24x7 software phone support, software updates + 4 hour Hardware Exchange (HS677E)
- 4-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS678E)
- 4-year, 24x7 software phone support, software updates + 4 hour Hardware Exchange (HS679E)
- 5-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS680E)
- 5-year, 24x7 software phone support, software updates + 4 hour Hardware Exchange (HS681E)

Refer to the HP website at: www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

HP 5500-24G-PoE+ SI Switch with 2 Interface Slots (JG238A)

Ports	24 RJ-45 autosensing 10/100/1000 PoE+ ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T, IEEE 802.3at PoE+) Media Type: Auto-MDIX Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only 4 dual-personality ports; auto-sensing 10/100/1000Base-T or SFP 2 port expansion module slots 1 RJ-45 serial console port Supports a maximum of 24 autosensing 10/100/1000 ports	
Physical characteristics	Dimensions	17.32(w) x 16.54(d) x 1.72(h) in (43.99 x 42.01 x 4.37 cm) (1U height)
	Weight	13.21 lb (5.99 kg)
Memory and processor	128 MB SDRAM, 16 MB flash; packet buffer size: 2 MB	
Mounting	Mounts in an EIA standard 19-in. telco rack or equipment cabinet (hardware included)	
Performance	1000 Mb Latency	< 3.2 μ s
	10 Gbps Latency	< 2.6 μ s
	Throughput	up to 107.2 million pps
	Routing/Switching capacity	144 Gb/s
Environment	Operating temperature	32°F to 113°F (0°C to 45°C)
	Operating relative humidity	10% to 90%, noncondensing

Technical Specifications

	Nonoperating/Storage temperature	-40°F to 158°F (-40°C to 70°C)
	Nonoperating/Storage relative humidity	5% to 95%, noncondensing
	Acoustic	ISO 7779
Electrical characteristics	Maximum heat dissipation	290 BTU/hr (305.95 kJ/hr)
	Voltage	100-240 VAC
	DC voltage	-52 to -55 VDC
	Maximum power rating	455 W
	PoE power	370 W
	Frequency	50/60 Hz
	Notes	Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated. PoE power is the power supplied by the internal power supply. It is dependent on the type and quantity of power supplies and may be supplemented with the use of an external power supply (EPS).
Safety	UL 60950-1; EN 60825-1 Safety of Laser Products-Part 1; EN 60825-2 Safety of Laser Products-Part 2; IEC 60950-1; CAN/CSA-C22.2 No. 60950-1; EN 60950-1/A11; FDA 21 CFR Subchapter J; ROHS Compliance	
Emissions	FCC part 15 Class A; VCCI Class A; EN 55022 Class A; CISPR 22 Class A; ICES-003 Class A; ANSI C63.4 2003; ETSI EN 300 386 V1.3.3; AS/NZS CISPR22 Class A; EN 61000-3-2; EN 61000-3-3; EN 61000-4-2; EN 61000-4-3; EN 61000-4-4; EN 61000-4-5; EN 61000-4-6; EN 61000-4-11; EN 61000-3-2:2006; EN 61000-3-3:1995 +A1:2001 +A2:2005; EMC Directive 2004/108/EC; FCC (CFR 47, Part 15) Class A	
Management	IMC - Intelligent Management Center; command-line interface; Web browser; SNMP Manager	
Services	3-year, 4-hour onsite, 13x5 coverage for hardware (UV870E) 3-year, 4-hour onsite, 24x7 coverage for hardware (UV873E) 3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 SW phone support and SW updates (UV876E) 3-year, 24x7 SW phone support, software updates (UV879E) 4-year, 4-hour onsite, 13x5 coverage for hardware (UV871E) 4-year, 4-hour onsite, 24x7 coverage for hardware (UV874E) 4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UV877E) 4-year, 24x7 SW phone support, software updates (UV880E) 5-year, 4-hour onsite, 13x5 coverage for hardware (UV872E) 5-year, 4-hour onsite, 24x7 coverage for hardware (UV875E) 5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UV878E) 5-year, 24x7 SW phone support, software updates (UV881E) 3 Yr 6 hr Call-to-Repair Onsite (UW966E) 4 Yr 6 hr Call-to-Repair Onsite (UW967E) 5 Yr 6 hr Call-to-Repair Onsite (UW968E)	

Refer to the HP website at: www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Technical Specifications

Ports	48 RJ-45 autosensing 10/100/1000 PoE+ ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T, IEEE 802.3at PoE+) Media Type: Auto-MDIX Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only 4 dual-personality ports; auto-sensing 10/100/1000Base-T or SFP 2 port expansion module slots 1 RJ-45 serial console port Supports a maximum of 48 autosensing 10/100/1000 ports	
Physical characteristics	Dimensions	17.32(w) x 16.54(d) x 1.72(h) in (43.99 x 42.01 x 4.37 cm) (1U height)
	Weight	16.53 lb (7.5 kg)
Memory and processor	128 MB SDRAM, 16 MB flash; packet buffer size: 4 MB	
Mounting	Mounts in an EIA standard 19-in. telco rack or equipment cabinet (hardware included)	
Performance	1000 Mb Latency	< 3.2 μ s
	10 Gbps Latency	< 2.6 μ s
	Throughput	up to 142.9 million pps
	Routing/Switching capacity	192 Gb/s
Environment	Operating temperature	32°F to 113°F (0°C to 45°C)
	Operating relative humidity	10% to 90%, noncondensing
	Nonoperating/Storage temperature	-40°F to 158°F (-40°C to 70°C)
	Nonoperating/Storage relative humidity	5% to 95%, noncondensing
	Acoustic	ISO 7779
Electrical characteristics	Maximum heat dissipation	444 BTU/hr (468.42 kJ/hr)
	Voltage	100-240 VAC
	DC voltage	-52 to -55 VDC
	Maximum power rating	870 W
	PoE power	740 W
	Frequency	50/60 Hz
	Notes	Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated. PoE power is the power supplied by the internal power supply. It is dependent on the type and quantity of power supplies and may be supplemented with the use of an external power supply (EPS). With AC input: the maximum power consumption is 500 W; PoE power is 370 W.
Safety	UL 60950-1; EN 60825-1 Safety of Laser Products-Part 1; EN 60825-2 Safety of Laser Products-Part 2; IEC 60950-1; CAN/CSA-C22.2 No. 60950-1; EN 60950-1/A11; FDA 21 CFR Subchapter J; ROHS Compliance	

Technical Specifications

Emissions	FCC part 15 Class A; VCCI Class A; EN 55022 Class A; CISPR 22 Class A; ICES-003 Class A; ANSI C63.4 2003; ETSI EN 300 386 V1.3.3; AS/NZS CISPR22 Class A; EN 61000-3-2; EN 61000-3-3; EN 61000-4-2; EN 61000-4-3; EN 61000-4-4; EN 61000-4-5; EN 61000-4-6; EN 61000-4-11; EN 61000-3-2:2006; EN 61000-3-3:1995 +A1:2001+A2:2005; EMC Directive 2004/108/EC; FCC (CFR 47, Part 15) Class A
Management	IMC - Intelligent Management Center; command-line interface; Web browser; SNMP Manager
Services	3-year, 4-hour onsite, 13x5 coverage for hardware (HQ080E) 3-year, 4-hour onsite, 24x7 coverage for hardware (HQ081E) 3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 SW phone support and SW updates (HQ084E) 3-year, 24x7 SW phone support, software updates (HQ083E) 4-year, 4-hour onsite, 13x5 coverage for hardware (HQ085E) 4-year, 4-hour onsite, 24x7 coverage for hardware (HQ086E) 4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (HQ093E) 4-year, 24x7 SW phone support, software updates (HQ091E) 5-year, 4-hour onsite, 13x5 coverage for hardware (HQ088E) 5-year, 4-hour onsite, 24x7 coverage for hardware (HQ089E) 5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (HQ094E) 5-year, 24x7 SW phone support, software updates (HQ092E) 3 Yr 6 hr Call-to-Repair Onsite (HQ082E) 4 Yr 6 hr Call-to-Repair Onsite (HQ087E) 5 Yr 6 hr Call-to-Repair Onsite (HQ090E)

Refer to the HP website at: www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Standards and protocols (applies to all products in series)

Device management

RFC 1157 SNMPv1/v2c
RFC 1305 NTPv3
RFC 1901 (Community based SNMPv2)
RFC 2452 MIB for TCP6
RFC 2454 MIB for UDP6
RFC 2573 (SNMPv3 Applications)
RFC 2576 (Coexistence between SNMP V1, V2, V3)
RFC 2819 RMON
RFC 3410 (Management Framework)
RFC 3416 (SNMP Protocol Operations v2)
RFC 3417 (SNMP Transport Mappings)
HTML and telnet management
Multiple Configuration Files
SNMP v3 and RMON RFC support
SSHv1/SSHv2 Secure Shell

General protocols

IEEE 802.1ad Q-in-Q
IEEE 802.1D MAC Bridges
IEEE 802.1p Priority
IEEE 802.1Q (GVRP)
IEEE 802.1s (MSTP)
IEEE 802.1w Rapid Reconfiguration of Spanning

RFC 2710 Multicast Listener Discovery (MLD) for IPv6
RFC 2893 Transition Mechanisms for IPv6 Hosts and Routers
RFC 2925 Definitions of Managed Objects for Remote Ping, Traceroute, and Lookup Operations (Ping only)
RFC 3056 Connection of IPv6 Domains via IPv4 Clouds
RFC 3162 RADIUS and IPv6
RFC 3306 Unicast-Prefix-based IPv6 Multicast Addresses
RFC 3315 DHCPv6 (client and relay)
RFC 3484 Default Address Selection for IPv6
RFC 3493 Basic Socket Interface Extensions for IPv6
RFC 3513 IPv6 Addressing Architecture
RFC 3542 Advanced Sockets API for IPv6
RFC 3587 IPv6 Global Unicast Address Format
RFC 3596 DNS Extension for IPv6
RFC 3810 MLDv2 for IPv6
RFC 4113 MIB for UDP
RFC 4443 ICMPv6

MIBs

RFC 1212 Concise MIB Definitions

Technical Specifications

Tree	RFC 1213 MIB II
IEEE 802.3ab 1000BASE-T	RFC 1724 RIPv2 MIB
IEEE 802.3ad Link Aggregation (LAG)	RFC 1757 Remote Network Monitoring MIB
IEEE 802.3ae 10-Gigabit Ethernet	RFC 2012 SNMPv2 MIB for TCP
IEEE 802.3af Power over Ethernet	RFC 2013 SNMPv2 MIB for UDP
IEEE 802.3i 10BASE-T	RFC 2233 Interface MIB
IEEE 802.3u 100BASE-X	RFC 2452 IPV6-TCP-MIB
IEEE 802.3x Flow Control	RFC 2454 IPV6-UDP-MIB
IEEE 802.3z 1000BASE-X	RFC 2465 IPV6 MIB
RFC 791 IP	RFC 2466 ICMPv6 MIB
RFC 792 ICMP	RFC 2571 SNMP Framework MIB
RFC 793 TCP	RFC 2572 SNMP-MPD MIB
RFC 854 TELNET	RFC 2573 SNMP-Notification MIB
RFC 925 Multi-LAN Address Resolution	RFC 2573 SNMP-Target MIB
RFC 950 Internet Standard Subnetting Procedure	RFC 2574 SNMP USM MIB
RFC 951 BOOTP	RFC 2618 RADIUS Authentication Client MIB
RFC 1058 RIPv1	RFC 2620 RADIUS Accounting Client MIB
RFC 1122 Host Requirements	RFC 2819 RMON MIB
RFC 1141 Incremental updating of the Internet checksum	RFC 2925 Ping MIB
RFC 1213 Management Information Base for Network Management of TCP/IP-based internets	RFC 3414 SNMP-User based-SM MIB
RFC 1305 NTPv3	RFC 3415 SNMP-View based-ACM MIB
RFC 1350 TFTP Protocol (revision 2)	RFC 4113 UDP MIB
RFC 1519 CIDR	
RFC 1542 BOOTP Extensions	Network management
RFC 1723 RIP v2	IEEE 802.1AB Link Layer Discovery Protocol (LLDP)
RFC 1812 IPv4 Routing	IEEE 802.1D (STP)
RFC 1887 An Architecture for IPv6 Unicast Address Allocation	RFC 1157 SNMPv1
RFC 2131 DHCP	RFC 1212 Concise MIB definitions
RFC 2236 IGMP Snooping	RFC 1215 SNMP Generic traps
RFC 2375 IPv6 Multicast Address Assignments	RFC 1757 RMON 4 groups: Stats, History, Alarms and Events
RFC 2581 TCP Congestion Control	RFC 1901 SNMPv2 Introduction
RFC 2616 HTTP Compatibility v1.1	RFC 1918 Private Internet Address Allocation
RFC 2644 Directed Broadcast Control	RFC 2373 Remote Network Monitoring Management Information Base for High Capacity Networks
RFC 2865 Remote Authentication Dial In User Service (RADIUS)	RFC 2571 An Architecture for Describing SNMP Management Frameworks
RFC 2866 RADIUS Accounting	RFC 2572 Message Processing and Dispatching for the Simple Network Management Protocol (SNMP)
RFC 3246 Expedited Forwarding PHB	RFC 2573 SNMP Applications
RFC 3410 Applicability Statements for SNMP	RFC 2573 SNMPv3 Applications
RFC 3414 User-based Security Model (USM) for version 3 of the Simple Network Management Protocol (SNMPv3)	RFC 2574 SNMPv3 User-based Security Model (USM)
RFC 3415 View-based Access Control Model (VACM) for the Simple Network Management Protocol (SNMP)	RFC 2575 SNMPv3 View-based Access Control Model (VACM)
RFC 3417 Transport Mappings for the Simple Network Management Protocol (SNMP)	RFC 2576 Coexistence between SNMP versions
RFC 3484 Default Address Selection for Internet Protocol version 6 (IPv6)	RFC 2578 SMIv2
	RFC 2581 TCP6
	RFC 2819 Four groups of RMON: 1 (statistics), 2 (history), 3 (alarm) and 9 (events)

Technical Specifications

RFC 3493 Basic Socket Interface Extensions for IPv6
RFC 3542 Advanced Sockets Application Program Interface (API) for IPv6
RFC 3587 IPv6 Global Unicast Address Format
RFC 3596 DNS Extensions to Support IP Version 6
RFC 4113 Management Information Base for the User Datagram Protocol (UDP)
RFC 4213 Basic IPv6 Transition Mechanisms
RFC 4443 Internet Control Message Protocol (ICMPv6) for the Internet Protocol Version 6 (IPv6) Specification
802.1r - GARP Proprietary Attribute Registration Protocol (GPRP)

IPv6

RFC 1887 IPv6 Unicast Address Allocation Architecture
RFC 1981 IPv6 Path MTU Discovery
RFC 2080 RIPng for IPv6
RFC 2373 IPv6 Addressing Architecture
RFC 2375 IPv6 Multicast Address Assignments
RFC 2460 IPv6 Specification
RFC 2461 IPv6 Neighbor Discovery
RFC 2462 IPv6 Stateless Address Auto-configuration
RFC 2463 ICMPv6
RFC 2464 Transmission of IPv6 over Ethernet Networks
RFC 2475 IPv6 DiffServ Architecture

RFC 2925 Definitions of Managed Objects for Remote Ping, Traceroute, and Lookup Operations
RFC 3176 sFlow
RFC 3410 Introduction to Version 3 of the Internet-standard Network Management Framework
RFC 3414 SNMPv3 User-based Security Model (USM)
RFC 3415 SNMPv3 View-based Access Control Model VACM)
ANSI/TIA-1057 LLDP Media Endpoint Discovery (LLDP-MED)
SNMPv1/v2c/v3

QoS/CoS

IEEE 802.1P (CoS)
RFC 2474 DSCP DiffServ
RFC 2475 DiffServ Architecture
RFC 2597 DiffServ Assured Forwarding (AF)
RFC 2598 DiffServ Expedited Forwarding (EF)

Security

IEEE 802.1X Port Based Network Access Control
RFC 1492 TACACS+
RFC 1918 Address Allocation for Private Internets
RFC 2865 RADIUS Authentication
RFC 2866 RADIUS Accounting
Access Control Lists (ACLs)
MAC Authentication
Port Security
SSHv2 Secure Shell

Accessories

HP 5500 SI Switch Series accessories

Modules

HP 5500 2-port 10GbE XFP Module	JD359B
HP A5500/A5120-EI 2p 10-GbE CX4 Module	JD360B
HP 5500 1-port 10GbE XFP Module	JD361B
HP 5500/5120 2-port 10GbE SFP+ Module	JD368B
HP 5500/4800 2-port GbE SFP Module	JD367A
NEW HP 5500/5120 2-port 10GBASE-T Module (JG535A)	JG535A

Transceivers

HP X125 1G SFP LC LH40 1310nm Transceiver	JD061A
HP X120 1G SFP LC LH40 1550nm Transceiver	JD062A
HP X125 1G SFP LC LH70 Transceiver	JD063B
HP X130 SFP+ LC SR Transceiver	JD092B
HP X130 SFP+ LC LRM Transceiver	JD093B
HP X130 SFP+ LC LR Transceiver	JD094B
HP X130 10G XFP LC LR 1310nm Transceiver	JD108B
HP X130 10G XFP LC SR Transceiver	JD117B
HP X120 1G SFP LC SX Transceiver	JD118B
HP X120 1G SFP LC LX Transceiver	JD119B
HP X135 10G XFP LC ER Transceiver	JD121A
HP X240 SFP+ to SFP+ 0.65 m Direct Attach Copper Cable	JD095C
HP X240 SFP+ to SFP+ 1.2 m Direct Attach Copper Cable	JD096C
HP X240 SFP+ to SFP+ 3 m Direct Attach Copper Cable	JD097C
HP X120 1G SFP LC BX 10-U Transceiver	JD098B
HP X120 1G SFP LC BX 10-D Transceiver	JD099B
HP X125 1G SFP RJ45 T Transceiver	JD089B
HP X130 10G SFP+ LC ER 40 km Transceiver	JG234A

Cables

HP X230 Local Connect 100 cm CX4 Cable	JD364B
HP X230 Local Connect CX4 300 cm Cable	JD365A
HP 0.5 m Multimode OM3 LC/LC Optical Cable	AJ833A
HP 1 m Multimode OM3 LC/LC Optical Cable	AJ834A
HP 2 m Multimode OM3 LC/LC Optical Cable	AJ835A
HP 5 m Multimode OM3 LC/LC Optical Cable	AJ836A
HP 15 m Multimode OM3 LC/LC Optical Cable	AJ837A
HP 30 m Multimode OM3 LC/LC Optical Cable	AJ838A
HP 50 m Multimode OM3 LC/LC Optical Cable	AJ839A
HP Premier Flex LC/LC Multi-mode OM4 2 fiber 1m Cable	QK732A
HP Premier Flex LC/LC Multi-mode OM4 2 fiber 2m Cable	QK733A
HP Premier Flex LC/LC Multi-mode OM4 2 fiber 5m Cable	QK734A
HP Premier Flex LC/LC Multi-mode OM4 2 fiber 15m Cable	QK735A
HP Premier Flex LC/LC Multi-mode OM4 2 fiber 30m Cable	QK736A
HP Premier Flex LC/LC Multi-mode OM4 2 fiber 50m Cable	QK737A
HP X230 Local Connect 50cm CX4 Cable	JD363B

Power Supply

Accessories

HP RPS800 Redundant Power System	JD183A
HP RPS1600 Redundant Power System	JG136A
HP RPS1600 1600W AC Power Supply	JG137A
Power cords	
HP X290 JD5 JD5 2m RPS1600 Cable	JD187A
HP X290 H2.7 H2.7 1m RPS800 Cable	JD184A

Accessory Product Details

NOTE: Details are not available for all accessories. The following specifications were available at the time of publication.

HP 5500 2-port 10GbE XFP Ports Module (JD359B)	Ports	2 XFP 10-GbE ports; Duplex: full only
	Services	Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

HP 5500 1-port 10GbE XFP Ports Module (JD361B)	Ports	1 XFP 10-GbE port; Duplex: full only
	Services	Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

HP 5500/4800 2-port GbE SFP Module (JD367A)	Ports	2 SFP 1000 Mbps ports
	Services	Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

HP X125 1G SFP LC LH40 1310nm Transceiver (JD061A) A small form-factor pluggable SFP Gigabit LH40 transceiver that provides a full duplex Gigabit solution up to 40km on a single-mode fiber.	Ports	1 LC 1000Base-LH port (no IEEE standard exists for 1550 nm optics)	
	Connectivity	Connector type	LC
		Wavelength	1310 nm
	Physical characteristics	Dimensions	2.17(d) x 0.6(w) x 0.46(h) in. (5.51 x 1.52 x 1.17 cm)
		Full configuration weight	0.04 lb. (0.02 kg)
	Electrical characteristics	Power consumption typical	0.8 W
		Power consumption maximum	1.0 W
	Cabling	Cable type:	Single-mode fiber optic, complying with ITU-T G.652;
Maximum distance:		<ul style="list-style-type: none"> 40km distance 	
Services	Fiber type	Single Mode	
		Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.	

Accessory Product Details

HP X120 1G SFP LC LH40 1550nm Transceiver (JD062A)	Ports	1 LC 1000BASE-LH port (no IEEE standard exists for 1550 nm optics)	
	Connectivity	Connector type	LC
A small form-factor pluggable (SFP) Gigabit LH40 transceiver that provides a full-duplex Gigabit solution up to 40 km on a single mode fiber.	Physical characteristics	Wavelength	1550 nm
	Electrical characteristics	Dimensions	2.17(d) x 0.6(w) x 0.46(h) in. (5.51 x 1.52 x 1.17 cm)
		Full configuration weight	0.04 lb. (0.02 kg)
Cabling	Power consumption typical	0.8 W	
Services	Power consumption maximum	1.0 W	
	Cabling	Cable type: Single-mode fiber optic, complying with ITU-T G.652;	
	Services	Maximum distance:	
	Services	<ul style="list-style-type: none"> • 40km distance 	
Services	Fiber type	Single Mode	
Services	Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.		

HP X125 1G SFP LC LH70 Transceiver (JD063B)	Ports	1 LC 1000BASE-LH port (no IEEE standard exists for 1550 nm optics)	
	Connectivity	Connector type	LC
A small form-factor pluggable (SFP) Gigabit LH70 transceiver that provides a full-duplex Gigabit solution up to 70km on a single-mode fiber.	Physical characteristics	Wavelength	1550 nm
	Electrical characteristics	Dimensions	2.17(d) x 0.6(w) x 0.46(h) in. (5.51 x 1.52 x 1.17 cm)
		Full configuration weight	0.04 lb. (0.02 kg)
Cabling	Power consumption typical	0.8 W	
Services	Power consumption maximum	1.0 W	
	Cabling	Cable type: Single-mode fiber optic, complying with ITU-T G.652;	
	Services	Maximum distance:	
	Services	<ul style="list-style-type: none"> • 70km 	
Services	Fiber type	Single Mode	
Services	Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.		

Accessory Product Details

HP X120 1G SFP LC SX Transceiver (JD118B)	Ports	1 LC 1000BASE-SX port
	Connectivity	Connector type LC
A small form-factor pluggable (SFP) Gigabit SX transceiver that provides a full-duplex Gigabit solution up to 550m on a Multimode fiber.	Physical characteristics	Wavelength 850 nm Dimensions 2.17(d) x 0.6(w) x 0.46(h) in. (5.51 x 1.52 x 1.17 cm)
	Electrical characteristics	Full configuration weight 0.04 lb. (0.02 kg) Power consumption typical 0.8 W Power consumption maximum 1.0 W
Cabling	Maximum distance: <ul style="list-style-type: none"> • FDDI Grade distance = 220m • OM1 = 275m • OM2 = 500m • OM3 = Not Specified by standard Cable length up to 550m Fiber type Multi Mode	
Services	Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.	

HP X120 1G SFP LC LX Transceiver (JD119B)	Ports	1 SFP 1000BASE-LX port (IEEE 802.3z Type 1000BASE-LX)
	Connectivity	Connector type LC
A small form-factor pluggable (SFP) Gigabit LX transceiver that provides a full duplex Gigabit solution up to 550m on MMF or 10Km on SMF	Physical characteristics	Wavelength 1300 nm Dimensions 2.17(d) x 0.6(w) x 0.46(h) in. (5.51 x 1.52 x 1.17 cm)
	Electrical characteristics	Full configuration weight 0.04 lb. (0.02 kg) Power consumption typical 0.8 W Power consumption maximum 1.0 W
Cabling	Cable type: Either single mode or multimode; Maximum distance: <ul style="list-style-type: none"> • 550m for Multimode • 10km for Singlemode Fiber type Both	
Services	Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.	

Accessory Product Details

<p>HP X120 1G SFP LC BX 10-U Transceiver (JD098B)</p> <p>A small form-factor pluggable (SFP) Gigabit LX-BX10-U transceiver that provides a full duplex Gigabit solution up to 10km on a single mode cable.</p>	<p>Ports</p> <p>1 LC 1000BASE-BX10 port (IEEE 802.3ah Type 1000BASE-BX10-U); Duplex: full only</p> <p>Connectivity</p> <p>Connector type LC</p> <p>Physical characteristics</p> <p>Dimensions 2.17(d) x 0.6(w) x 0.46(h) in. (5.51 x 1.52 x 1.17 cm)</p> <p>Full configuration weight 0.04 lb. (0.02 kg)</p> <p>Electrical characteristics</p> <p>Power consumption typical 0.8 W</p> <p>Power consumption maximum 1.0 W</p> <p>Cabling</p> <p>Maximum distance:</p> <ul style="list-style-type: none"> • 10km <p>Fiber type Single Mode</p> <p>Notes</p> <p>TX 1310nm RX 1490nm</p> <p>Services</p> <p>Refer to the HP website at: www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.</p>
---	---

<p>HP X120 1G SFP LC BX 10-D Transceiver (JD099B)</p> <p>A small form-factor pluggable (SFP) Gigabit LX-BX10-D transceiver that provides a full duplex Gigabit solution up to 10km on a single mode cable.</p>	<p>Ports</p> <p>1 LC 1000BASE-BX10 port (IEEE 802.3ah Type 1000BASE-BX10-D); Duplex: full only</p> <p>Connectivity</p> <p>Connector type LC</p> <p>Physical characteristics</p> <p>Dimensions 2.17(d) x 0.6(w) x 0.46(h) in. (5.51 x 1.52 x 1.17 cm)</p> <p>Full configuration weight 0.04 lb. (0.02 kg)</p> <p>Electrical characteristics</p> <p>Power consumption typical 0.8 W</p> <p>Power consumption maximum 1.0 W</p> <p>Cabling</p> <p>Maximum distance:</p> <ul style="list-style-type: none"> • Up to 10km <p>Fiber type Single Mode</p> <p>Notes</p> <p>TX 1490nm RX 1310nm</p> <p>Services</p> <p>Refer to the HP website at: www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.</p>
---	---

Accessory Product Details

HP X125 1G SFP RJ45 T Transceiver (JD089B)

A small form factor pluggable (SFP) Gigabit 1000Base-T transceiver that provides a full duplex Gigabit solution up to 100m on a Cat-5+ cable.

Ports	1 RJ-45 1000BASE-T port (IEEE 802.3ab Type 1000BASE-T)
Connectivity	Connector type RJ-45
Physical characteristics	Dimensions 2.71(d) x 0.54(w) x 0.55(h) in. (6.88 x 1.37 x 1.4 cm) Full configuration weight 0.07 lb. (0.03 kg)
Electrical characteristics	Power consumption typical 0.8 W Power consumption maximum 1.0 W
Cabling	Cable type: 1000BASE-T: Category 5 (5E or better recommended), 100 Ω differential 4-pair unshielded twisted pair (UTP) or shielded twisted pair (STP) balanced, complying with IEEE 802.3ab 1000BASE-T; Maximum distance: • 100m
Services	Refer to the HP website at: www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

HP 0.5 m Multimode OM3 LC/LC Optical Cable (AJ833A)

Cabling	Cable type: 50/125 μm (core/cladding) diameter, multimode fiber optic, with effective modal bandwidth of 2000 MHz/km as detailed in TIA-492AAAC for distances of up to 300 m
Notes	Maximum distance: 10Gbps Transfer Rate (Ethernet): 300m Cable Specs: Tight buffered duplex fiber optic multimode OM3 50/125 μm fiber optic cable and Ethernet assembly with LC duplex connectors on one end and LC duplex connectors on other end. <ul style="list-style-type: none"> ● Dimensions: Core diameter: 50 ± 3.0μm Cladding diameter: 125 ± 2.0μm Coating diameter: 245 ± 10μm ● Optical glass: Bandwidth: For LED sources: 1500/500 MHz-km @850/1300nm. ● Optical glass: Bandwidth: For Laser sources: 2000/500 MHz-km @850/1300nm. VCSEL Laser sources: 600 / 600 meters @850/1300nm for Gigabit Ethernet compliant links. ● CABLE: The cable is duplex zipcord graded index 50/125μm multimode optical fiber and designed to work in both the 850 and 1300 nm wavelength windows. ● BULK CABLE & CABLE ASSEMBLY CONFIGURATION: ● Jacket Material: Riser Grade - Low Smoke Zero Halogen thermoplastic. ● Jacket Color: Aqua for OM3 multimode per TIA 598 ● Boot Color: White ● Insertion Loss: less than 0.5 dB @ 850 with LED source, 0.003 dB/M added for lengths > 30 meters. ● Maximum Cable attenuation: 3.0 dB/km @ 850 nm, 1.0 dB/Km @ 1310

Accessory Product Details

Services

nm @ 23°C as tested in accordance with EIA 455-46.

- Weight: Air Packed Weight: 1 LB Net Weight: 0.454Kg

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

HP 1 m Multimode OM3 LC/LC Optical Cable (AJ834A)

Cabling

Cable type:

50/125 µm (core/cladding) diameter, multimode fiber optic, with effective modal bandwidth of 2000 MHz/km as detailed in TIA-492AAAC for distances of up to 300 m

Maximum distance:

10Gbps Transfer Rate (Ethernet): 300m

Notes

Cable Specs: Tight buffered duplex fiber optic multimode OM3 50/125 µm fiber optic cable and Ethernet assembly with LC duplex connectors on one end and LC duplex connectors on other end.

- Dimensions: Core diameter: 50 ± 3.0µm Cladding diameter: 125 ± 2.0µm Coating diameter: 245 ± 10µm
- Optical Glass Bandwidth: For LED sources: 1500/500 MHz-km @850/1300nm.
- Optical Glass: For Laser sources: 2000/500 MHz-km @850/1300nm. VCSEL Laser sources: Shall achieve 600 / 600 meters @850/1300nm for Gigabit Ethernet compliant links.
- CABLE: The cable is duplex zipcord graded index 50/125µm multimode optical fiber. The cable is designed to work in both the 850 and 1300 nm wavelength windows.
- BULK CABLE & CABLE ASSEMBLY CONFIGURATION:
- Jacket Material: Riser Grade - Low Smoke Zero Halogen thermoplastic.
- Jacket Color: Aqua for OM3 multimode per TIA 598
- Boot Color: White
- Insertion Loss: less than 0.5 dB @ 850 with LED source, 0.003 dB/M added for lengths > 30 meters.
- Maximum Cable attenuation: 3.0 dB/km @ 850 nm, 1.0 dB/Km @ 1310 nm @ 23°C as tested in accordance with EIA 455-46.
- Weight: Air Packed Weight: 1 LB Net Weight: 0.454Kg

Services

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Accessory Product Details

HP 2 m Multimode OM3 LC/LC Optical Cable
(AJ835A) **Cabling**

Cable type:

50/125 µm (core/cladding) diameter, multimode fiber optic, with effective modal bandwidth of 2000 MHz/km as detailed in TIA-492AAAC for distances of up to 300 m;

Maximum distance:

10Gbps Transfer Rate (Ethernet): 300m

Notes

Cable Specs: Tight buffered duplex fiber optic multimode OM3 50/125 µm fiber optic cable and Ethernet assembly with LC duplex connectors on one end and LC duplex connectors on other end.

- Dimensions: Core diameter: 50 ± 3.0µm Cladding diameter: 125 ± 2.0µm Coating diameter: 245 ± 10µm
- Optical Glass Bandwidth: For LED sources: 1500/500 MHz-km @850/1300nm.
- Optical Glass: For Laser sources: 2000/500 MHz-km @850/1300nm. VCSEL Laser sources: Shall achieve 600 / 600 meters @850/1300nm for Gigabit Ethernet compliant links.
- CABLE: The cable is duplex zipcord graded index 50/125µm multimode optical fiber. The cable is designed to work in both the 850 and 1300 nm wavelength windows.
- BULK CABLE & CABLE ASSEMBLY CONFIGURATION:
- Jacket Material: Riser Grade - Low Smoke Zero Halogen thermoplastic.
- Jacket Color: Aqua for OM3 multimode per TIA 598
- Boot Color: White
- Insertion Loss: less than 0.5 dB @ 850 with LED source, 0.003 dB/M added for lengths > 30 meters.
- Maximum Cable attenuation: 3.0 dB/km @ 850 nm, 1.0 dB/Km @ 1310 nm @ 23°C as tested in accordance with EIA 455-46.
- Weight: Air Packed Weight: 1 LB Net Weight: 0.454Kg

Services

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Accessory Product Details

HP 5 m Multimode OM3 LC/LC Optical Cable **Cabling**
(AJ836A)

Cable type:

50/125 µm core/cladding) diameter, multimode fiber optic, with effective modal bandwidth of 2000 MHz/km as detailed in TIA-492AAAC for distances of up to 300 m;

Maximum distance:

10Gbps Transfer Rate (Ethernet): 300m

Notes

Cable Specs: This specification defines the detail requirements for a tight buffered duplex fiber optic multimode OM3 50/125 um fiber optic cable and Ethernet assembly with LC duplex connectors on one end and LC duplex connectors on other end.

- Dimensions: Core diameter: 50 ± 3.0um Cladding diameter: 125 ± 2.0um Coating diameter: 245 ± 10um
- Optical Glass Bandwidth: For LED sources: 1500/500 MHz-km @850/1300nm.
- Optical Glass: For Laser sources: 2000/500 MHz-km @850/1300nm. VCSEL Laser sources: Shall achieve 600 / 600 meters @850/1300nm for Gigabit Ethernet compliant links.
- CABLE: The cable is duplex zipcord graded index 50/125um multimode optical fiber. The cable is designed to work in both the 850 and 1300 nm wavelength windows.
- BULK CABLE & CABLE ASSEMBLY CONFIGURATION:
- Jacket Material: Riser Grade - Low Smoke Zero Halogen thermoplastic.
- Jacket Color: Aqua for OM3 multimode per TIA 598
- Boot Color: White
- Insertion Loss: less than 0.5 dB @ 850 with LED source, 0.003 dB/M added for lengths > 30 meters.
- Maximum Cable attenuation: 3.0 dB/km @ 850 nm, 1.0 dB/Km @ 1310 nm @ 23°C as tested in accordance with EIA 455-46.
- Weight: Air Packed Weight: 1 LB Net Weight: 0.454Kg

Services

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Accessory Product Details

HP 15 m Multimode OM3 Cabling
LC/LC Optical Cable
(AJ837A)

Cable type:

50/125 µm (core/cladding) diameter, multimode fiber optic, with effective modal bandwidth of 2000 MHz/km as detailed in TIA-492AAAC for distances of up to 300 m;

Maximum distance:

10Gbps Transfer Rate (Ethernet): 300m

Notes

Cable Specs: Tight buffered duplex fiber optic multimode OM3 50/125 µm fiber optic cable and Ethernet assembly with LC duplex connectors on one end and LC duplex connectors on other end.

- Dimensions: Core diameter: 50 ± 3.0µm Cladding diameter: 125 ± 2.0µm Coating diameter: 245 ± 10µm
- Optical Glass Bandwidth: For LED sources: 1500/500 MHz-km @850/1300nm.
- Optical Glass: For Laser sources: 2000/500 MHz-km @850/1300nm. VCSEL Laser sources: Shall achieve 600 / 600 meters @850/1300nm for Gigabit Ethernet compliant links.
- CABLE: The cable is duplex zipcord graded index 50/125µm multimode optical fiber. The cable is designed to work in both the 850 and 1300 nm wavelength windows.
- BULK CABLE & CABLE ASSEMBLY CONFIGURATION:
- Jacket Material: Riser Grade - Low Smoke Zero Halogen thermoplastic.
- Jacket Color: Aqua for OM3 multimode per TIA 598
- Boot Color: White
- Insertion Loss: less than 0.5 dB @ 850 with LED source, 0.003 dB/M added for lengths > 30 meters.
- Maximum Cable attenuation: 3.0 dB/km @ 850 nm, 1.0 dB/Km @ 1310 nm @ 23°C as tested in accordance with EIA 455-46.
- Weight: Air Packed Weight: 1 LB Net Weight: 0.454Kg

Services

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Accessory Product Details

HP 30 m Multimode OM3 Cabling
LC/LC Optical Cable
(AJ838A)

Cable type:

50/125 µm (core/cladding) diameter, multimode fiber optic, with effective modal bandwidth of 2000 MHz/km as detailed in TIA-492AAAC for distances of up to 300 m;

Maximum distance:

10Gbps Transfer Rate (Ethernet): 300m

Notes

Cable Specs: Tight buffered duplex fiber optic multimode OM3 50/125 µm fiber optic cable and Ethernet assembly with LC duplex connectors on one end and LC duplex connectors on other end.

- Dimensions: Core diameter: 50 ± 3.0µm Cladding diameter: 125 ± 2.0µm Coating diameter: 245 ± 10µm
- Optical Glass Bandwidth: For LED sources: 1500/500 MHz-km @850/1300nm.
- Optical Glass: For Laser sources: 2000/500 MHz-km @850/1300nm. VCSEL Laser sources: Shall achieve 600 / 600 meters @850/1300nm for Gigabit Ethernet compliant links.
- CABLE: The cable is duplex zipcord graded index 50/125µm multimode optical fiber. The cable is designed to work in both the 850 and 1300 nm wavelength windows.
- BULK CABLE & CABLE ASSEMBLY CONFIGURATION:
- Jacket Material: Riser Grade - Low Smoke Zero Halogen thermoplastic.
- Jacket Color: Aqua for OM3 multimode per TIA 598
- Boot Color: White
- Insertion Loss: less than 0.5 dB @ 850 with LED source, 0.003 dB/M added for lengths > 30 meters.
- Maximum Cable attenuation: 3.0 dB/km @ 850 nm, 1.0 dB/Km @ 1310 nm @ 23°C as tested in accordance with EIA 455-46.
- Weight: Air Packed Weight: 1 LB Net Weight: 0.454Kg

Services

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Accessory Product Details

HP 50 m Multimode OM3 Cabling
LC/LC Optical Cable
(AJ839A)

Cable type:

50/125 µm (core/cladding) diameter, multimode fiber optic, with effective modal bandwidth of 2000 MHz/km as detailed in TIA-492AAAC for distances of up to 300 m;

Maximum distance:

10Gbps Transfer Rate (Ethernet): 300m

Notes

Cable Specs: Tight buffered duplex fiber optic multimode OM3 50/125 µm fiber optic cable and Ethernet assembly with LC duplex connectors on one end and LC duplex connectors on other end.

- Dimensions: Core diameter: 50 ± 3.0µm Cladding diameter: 125 ± 2.0µm Coating diameter: 245 ± 10µm
- Optical Glass Bandwidth: For LED sources: 1500/500 MHz-km @850/1300nm.
- Optical Glass: For Laser sources: 2000/500 MHz-km @850/1300nm. VCSEL Laser sources: Shall achieve 600 / 600 meters @850/1300nm for Gigabit Ethernet compliant links.
- CABLE: The cable is duplex zipcord graded index 50/125µm multimode optical fiber. The cable is designed to work in both the 850 and 1300 nm wavelength windows.
- BULK CABLE & CABLE ASSEMBLY CONFIGURATION:
- Jacket Material: Riser Grade - Low Smoke Zero Halogen thermoplastic.
- Jacket Color: Aqua for OM3 multimode per TIA 598
- Boot Color: White
- Insertion Loss: less than 0.5 dB @ 850 with LED source, 0.003 dB/M added for lengths > 30 meters.
- Maximum Cable attenuation: 3.0 dB/km @ 850 nm, 1.0 dB/Km @ 1310 nm @ 23°C as tested in accordance with EIA 455-46.
- Weight: Air Packed Weight: 1 LB Net Weight: 0.454Kg

Services

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Accessory Product Details

**HP Premier Flex LC/LC
Multi-mode OM4 2 fiber
1m Cable (QK732A)**

Notes

Cable Specs: Graded-index, "bendable" fiber optic multimode OM3+ 50/125um duplex cable and Ethernet assembly with LC duplex connectors on each end.

- Core Diameter: 50um ±3um, Cladding diameter: 125um ±2um; Coating diameter: 245 ± 10um
- Bandwidth: 3000 MHz-km @ 850nm (Laser)
- Jacket Color: Blue
- Jacket Material: Riser Grade – Low Smoke Zero Halogen (LSZH) thermoplastic
- Boot Color: White
- Outer Jacket Print: HP PremierFlex OM3+ Fiber Optic Cable, 50/125um, Type OFNR (UL), LSZH, cUL, OFN FT4, ROHS. Cable also has a longitudinal white stripe that runs the entire length of the cable.
- Insertion Loss: Less than 0.5dB @ 850nm with LED source, 0.003dB/m added for lengths >30m
- Maximum Cable Attenuation: 3.0 dB/km @ 850nm, 1.0 dB/km @ 1310nm @ 23°C as tested in accordance with EIA 455-45

Services

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

**HP Premier Flex LC/LC
Multi-mode OM4 2 fiber
2m Cable (QK733A)**

Notes

Cable Specs: Graded-index, "bendable" fiber optic multimode OM3+ 50/125um duplex cable and Ethernet assembly with LC duplex connectors on each end.

- Core diameter: 50um ±3um, Cladding diameter: 125um ±2um; Coating diameter: 245 ± 10um
- Bandwidth: 3000 MHz-km @ 850nm (Laser)
- Jacket Color: Blue
- Jacket Material: Riser Grade – Low Smoke Zero Halogen (LSZH) thermoplastic
- Boot Color: White
- Outer Jacket Print: HP PremierFlex OM3+ Fiber Optic Cable, 50/125um, Type OFNR (UL), LSZH, cUL, OFN FT4, ROHS. Cable also has a longitudinal white stripe that runs the entire length of the cable.
- Insertion Loss: Less than 0.5dB @ 850nm with LED source, 0.003dB/m added for lengths >30m
- Maximum Cable Attenuation: 3.0 dB/km @ 850nm, 1.0 dB/km @ 1310nm @ 23°C as tested in accordance with EIA 455-45

Services

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Accessory Product Details

**HP Premier Flex LC/LC
Multi-mode OM4 2 fiber
5m Cable (QK734A)**

Notes

Cable Specs: Graded-index, "bendable" fiber optic multimode OM3+ 50/125um duplex cable and Ethernet assembly with LC duplex connectors on each end.

- Core diameter: 50um \pm 3um, Cladding diameter: 125um \pm 2um; Coating diameter: 245 \pm 10um
- Bandwidth: 3000 MHz-km @ 850nm (Laser)
- Jacket Color: Blue
- Jacket Material: Riser Grade – Low Smoke Zero Halogen (LSZH) thermoplastic
- Boot Color: White
- Outer Jacket Print: HP PremierFlex OM3+ Fiber Optic Cable, 50/125um, Type OFNR (UL), LSZH, cUL, OFN FT4, ROHS. Cable also has a longitudinal white stripe that runs the entire length of the cable.
- Insertion Loss: Less than 0.5dB @ 850nm with LED source, 0.003dB/m added for lengths >30m
- Maximum Cable Attenuation: 3.0 dB/km @ 850nm, 1.0 dB/km @ 1310nm @ 23°C as tested in accordance with EIA 455-45

Services

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

**HP Premier Flex LC/LC
Multi-mode OM4 2 fiber
15m Cable (QK735A)**

Notes

Cable Specs: Graded-index, "bendable" fiber optic multimode OM3+ 50/125um duplex cable and Ethernet assembly with LC duplex connectors on each end.

- Core diameter: 50um \pm 3um, Cladding diameter: 125um \pm 2um; Coating diameter: 245 \pm 10um
- Bandwidth: 3000 MHz-km @ 850nm (Laser)
- Jacket Color: Blue
- Jacket Material: Riser Grade – Low Smoke Zero Halogen (LSZH) thermoplastic
- Boot Color: White
- Outer Jacket Print: HP PremierFlex OM3+ Fiber Optic Cable, 50/125um, Type OFNR (UL), LSZH, cUL, OFN FT4, ROHS. Cable also has a longitudinal white stripe that runs the entire length of the cable.
- Insertion Loss: Less than 0.5dB @ 850nm with LED source, 0.003dB/m added for lengths >30m
- Maximum Cable Attenuation: 3.0 dB/km @ 850nm, 1.0 dB/km @ 1310nm @ 23°C as tested in accordance with EIA 455-45

Services

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Accessory Product Details

**HP Premier Flex LC/LC
Multi-mode OM4 2 fiber
30m Cable (QK736A)**

Notes

Cable Specs: Graded-index, "bendable" fiber optic multimode OM3+ 50/125um duplex cable and Ethernet assembly with LC duplex connectors on each end.

- Core diameter: 50um ±3um, Cladding diameter: 125um ±2um; Coating diameter: 245 ± 10um
- Bandwidth: 3000 MHz-km @ 850nm (Laser)
- Jacket Color: Blue
- Jacket Material: Riser Grade – Low Smoke Zero Halogen (LSZH) thermoplastic
- Boot Color: White
- Outer Jacket Print: HP PremierFlex OM3+ Fiber Optic Cable, 50/125um, Type OFNR (UL), LSZH, cUL, OFN FT4, ROHS. Cable also has a longitudinal white stripe that runs the entire length of the cable.
- Insertion Loss: Less than 0.5dB @ 850nm with LED source, 0.003dB/m added for lengths >30m
- Maximum Cable Attenuation: 3.0 dB/km @ 850nm, 1.0 dB/km @ 1310nm @ 23°C as tested in accordance with EIA 455-45

Services

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

**HP Premier Flex LC/LC
Multi-mode OM4 2 fiber
50m Cable (QK737A)**

Notes

Cable Specs: Graded-index, "bendable" fiber optic multimode OM3+ 50/125um duplex cable and Ethernet assembly with LC duplex connectors on each end.

- Core diameter: 50um ±3um, Cladding diameter: 125um ±2um; Coating diameter: 245 ± 10um
- Bandwidth: 3000 MHz-km @ 850nm (Laser)
- Jacket Color: Blue
- Jacket Material: Riser Grade – Low Smoke Zero Halogen (LSZH) thermoplastic
- Boot Color: White
- Outer Jacket Print: HP PremierFlex OM3+ Fiber Optic Cable, 50/125um, Type OFNR (UL), LSZH, cUL, OFN FT4, ROHS. Cable also has a longitudinal white stripe that runs the entire length of the cable.
- Insertion Loss: Less than 0.5dB @ 850nm with LED source, 0.003dB/m added for lengths >30m
- Maximum Cable Attenuation: 3.0 dB/km @ 850nm, 1.0 dB/km @ 1310nm @ 23°C as tested in accordance with EIA 455-45

Services

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Accessory Product Details

HP RPS1600 Redundant Power System (JG136A)	Ports	8 redundant power supply ports Restrictions: two -56V/25A DC(PoE); six -56V/8A DC(non-PoE)
	Physical characteristics	<p>Dimensions 15.63(d) x 17.32(w) x 1.74(h) in. (39.7 x 44 x 4.42 cm)</p> <p>Weight 14.11 lb. (6.4 kg)</p> <p>Full configuration weight 16.75 lb. (7.6 kg)</p>
	Environment	<p>Operating temperature 14°F to 122°F (-10°C to 50°C)</p> <p>Operating relative humidity 5% to 95%</p> <p>Nonoperating/Storage temperature -40°F to 158°F (-40°C to 70°C)</p> <p>Nonoperating/Storage relative humidity 5% to 95%</p> <p>Altitude up to 13,123 ft. (4 km)</p> <p>Acoustic Pressure: 53 dB; ISO 7779, ISO 9296</p>
	Electrical characteristics	<p>Voltage 100-120/200-240 VAC</p> <p>Current 30/60 A</p> <p>Idle power 38 W</p> <p>Maximum power rating 3550 W</p> <p>RPS power 3200 W</p> <p>PoE power 2800 W</p> <p>RPS -55 V</p> <p>PoE -55 V</p> <p>Frequency 50/60 Hz</p> <p>Notes Idle power is the actual power consumption of the device with no ports connected. Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated. With one RPS1600 Power Supply, the PRS1600 Redundant Power System can provide 1600W power output; With two PRS1600 Power Supplies, the output power is 3200W.</p>
	Safety	CE Labeled; UL 60950-1; IEC 60950-1; ICES-003; FCC Part 15, Subpart B; EU RoHS Compliant; EN 60950-1/A11; C-Tick; VCCI Class A; ROHS Compliance; EN 300386
	Services	Refer to the HP website at: www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Accessory Product Details

HP RPS1600 1600W AC Power Supply (JG137A)

Physical characteristics	Dimensions	8.19(d) x 4.96(w) x 1.63(h) in. (20.8 x 12.6 x 4.15 cm)
	Weight	3.02 lb. (1.37 kg)
Environment	Operating temperature	14°F to 122°F (-10°C to 50°C)
	Operating relative humidity	5% to 95%
	Nonoperating/Storage temperature	-40°F to 158°F (-40°C to 70°C)
	Nonoperating/Storage relative humidity	5% to 95%
Electrical characteristics	Voltage	100-120/200-240 VAC
	Current	15/30 A
	Maximum power rating	1600 W
	Frequency	50/60 Hz
	Notes	Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.
Services		Refer to the HP website at: www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

To learn more, visit: www.hp.com/networking

© Copyright 2010-2013 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.